


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED

- NOTES:
- FINAL RATIO RANGE: 2069.3 : 1 - 6952.8 : 1
 BASE RATIO: 27.25 : 1
 WORM GEAR REDUCER RATIO: 20.25 : 1
 AUXILLIARY SPUR RATIO RANGE: 3.75 : 1 - 12.6 : 1
 - MAX BORE & KEY: ϕ 10" W/2 1/2" X 2" KEY
 - MAX STEM ENGAGEMENT: 15 3/4"
 - APPROXIMATE WEIGHT: 2991 LBS
 - UNIT IS SHOWN IN THE OPEN POSITION

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DIMENSIONS ARE IN INCHES	DRAWN	JM 7/13/06
TOLERANCES:	CHECKED	
FRACTIONAL $\pm 1/32$	ENG APPR.	
ANGULAR: MACH $\pm 1/2$	MFG APPR.	
BEND $\pm 1/2$	Q.A.	
TWO PLACE DECIMAL $\pm .02$	COMMENTS:	
THREE PLACE DECIMAL $\pm .005$		

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MAX TORQUE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MAX TORQUE IS PROHIBITED.



TITLE MW2 MANUAL, GENERIC
 1500K TO 2250K IN-LBS

SIZE	DWG. NO.	REV.
B	300117	

SCALE: 1:12 WT: 2991 lbs SHEET 1 OF 1

Thursday, July 27, 2006 9:41:45 AM